



**grupo
estucalia**

+34 968 862 467
www.monocapas.com

DATA SHEET

FINISHING RESIN

EURO-PROTEC EM-100



Acrylic-styrene copolymer emulsion to protect single-layer mortars, with high resistance to water, alkalis and great thermal plasticity.

METHODOLOGY OF USE

Apply with a brush or roller on the finished surface of the monolayer mortar, trying to leave a uniform layer covering the entire surface.

STORAGE

Store in places protected from the sun or excessive heat sources. The container must be properly closed. It is advisable to use the product in its first year of life. Possibility of 5 or 15 liters containers.

CHARACTERISTICS:

Excellent properties as a water repellent
Reduces fouling of the facing and the proliferation of algae
Effective resistance to attack by alkalis.
Adequate resistance to ultraviolet rays

CONSERVATION:

12 months from the date of manufacture, in the original closed container and protected from moisture.

PRESENTATION:

Package of 5 or 15 liters approx.

COLOR RANGE

Colorless product gloss or matte finish

TECHNICAL DATA

Appearance	Colorless Liquid
Solids content	30 % (DIN 53819)
Viscosity	150 / 300 CP BROOKFIELD RVT 25º'ba C (ISO/DIS 2555)
Ph	8 / 8,5 (DIN 53785)
Nature	Organic
Free monomer	0,30%
Work temperature	+ 5º'ba to +65º'ba
Performance	10 / 11 m2/Ltr. (according to applied layers)
Base	Water Base. Non Toxic. Non Flammable

The instructions for use do not imply any commitment for the manufacturer, nor do they free the consumer from the examination and verification of the product for its correct application. The liability of the manufacturer will be limited, in any case, to the value of the merchandise used.

Camino Viejo de Fortuna, 40 · 30148 · Apartado Correos 162 · Matanzas-Santomera (Murcia)
T.: 968 862 467 · 663 519 854 · e-mail: estucalia@monocapas.com